

INFLATABLE TANK

Manufactured with **ultra-resistant PVC**, they can be deployed in just minutes and provide high-capacity water storage exactly where it is needed: fast, reliable, and built to last.

Thanks to **their two 3" threaded valves**, they connect easily to vft portable fire pumps, creating a powerful and efficient setup for both aerial and ground operations.

Whether **refilling a helibucket or supplying a hose line**, this system adapts to your operational needs.



Modular water supply system for aerial and ground firefighting operations.

Technical Specifications

Capacities	3.000L	7.000L	12.000L	25.000L	56.000L
Diameter	2 m 6.5 ft	3 m 9.8 ft	4 m 13 ft	4 m 13 ft	6 m 20 ft
Height	1 m 3.3 ft	1 m 3.3 ft	1 m 3.3 ft	2 m 6.5 ft	2 m 6.5 ft
Thickness	10 cm 4 in	10 cm 4 in	10 cm 4 in	10 cm 4 in	10 cm 4 in
Weight	31 kg 68 lbs	43 Kg 95 lbs	43 Kg 95 lbs	105,5 Kg 232 lbs	173,5 Kg 382 lbs
Water level indicator	Visual level indicator inside the tank	Visual level indicator inside the tank	Visual level indicator inside the tank	Visual float level indicator	Visual float level indicator
Material	PVC 2,600 g / m2	PVC 2,600 g / m2	PVC 2,600 g / m2	PVC 2,600 g / m2	PVC 2,600 g / m2
Connections	Two 2" threaded connections	Two 3" threaded valves	Two 3" threaded valves	Two 3" threaded valves	Two 3" threaded valves
Inflation time	1 min	1 min	2 min	3 min	4 min

Included components

- Repair kit.
- Anchoring kit.
- Blowers.
- Portable DeWalt blower with battery.
- Square base.
- Transport bag.
- Pressure gauge.
- Camlock cover bag.
- Charger for DeWalt batteries.



Optional components

- Reducers and adapters for the tank.
- Valves.
- Tank-to-pump connection hoses.
- Adapters for the pump.