



BRT FIRE & RESCUE SUPPLIES

4044 Revolver Select Flow Nozzle

SCO1.NO.4044 - Revolver Nozzle

SCO1.NO.4044SO - Revolver Nozzle with Shut off

- Outer barrel rotates easily to provide flow rates of 12, 15, 35 and 46 LPM. Plus OFF setting.
- Suitable for Class A or Class B Foams.
- Available in 25 & 38mm BSPF Inlet.
- Maximum operating pressure 10 BAR.



SCO1.NO.4044.STZ

SCO1.NO.4044SO.STZ

*SCO1.NO.4044 shown with Optional Stortz Adapter (Not Supplied as Standard)



SCO1.NO.4044

Inlet Pressure

	5/32" (3.96mm)	3/16" (4.76mm)	1/4" (6.35mm)	45° Fan
43.5 PSI (300 kPa)	3 GPM (11 lpm)	6.5 GPM (24 lpm)	12 GPM (45 lpm)	9 GPM (34 lpm)
58.01 PSI (400 kPa)	4 GPM (15 lpm)	8 GPM (30 lpm)	14 GPM (53 lpm)	12 GPM (45 lpm)
72.5 PSI (500 kPa)	5.5 GPM (20 lpm)	9 GPM (34 lpm)	16 GPM (60 lpm)	14 GPM (53 lpm)

Quality and Innovative Fire Rescue Equipment



"Quality and Innovative Fire and Rescue Equipment"

www.bigredtruck.com.au
asktheteam@bigredtruck.com.au
Phone: +61 (0)7 3287 5505