

# Municipal Electric Monitors

## DeckMaster Monitor 1250 GPM (4800 LPM)

The DeckMaster Monitor is a technologically advanced, electrically controlled deck monitor with automated elevating capability. The unique design of the DeckMaster Monitor allows electric elevation and positioning 26" above the base of the flange for operation over obstructions with the push of a switch.

### 3440 DeckMaster Electric Monitor

- 340° horizontal rotation with adjustable stops
- Vertical travel 90° above to 45° below horizontal
- Manual override for horizontal, vertical and elevation control
- Stow position set easily by the end user
- Automatic drain for freeze protection
- Diagnostic light for trouble-shooting
- Connection for deployed indicator light
- Available in 12 or 24 volt (Must specify)
- Optional position feedback (Must specify)
- See page 193 for Monitor/Fog Nozzle Compatibility Chart



Style 3440 Shown in a typical stowed position



Style 3440 Shown deployed with Style 1577 SaberMaster™ Nozzle

See page 45 for Electric Monitor Accessories

Style	Weight lbs. (kg)	In Stowed Position			Inlet	Outlet	Flow	
		Height	Width	Depth			GPM	LPM
3440	55 (25 kg)*	14 1/2" (368 mm)	16 3/4" (425 mm)	17" (431 mm)	3" FL (75 mm)	2 1/2" NH (65 mm)	1250	4800

\* Less Nozzle



Wireless Remote Control Available



**Combine with the Style 1577 SaberMaster nozzle to meet new NFPA 1901 recommendations to use remote control monitors for safe deck gun operations.**

Remote DeckMaster operation eliminates the need to have a firefighter on the deck to operate the monitor.



DeckMaster available with position feedback and position indicator option



## Electric Riser for DeckMaster & StreamMaster™

Overcome increased heights of apparatus bodies, raised roof cabs, and other obstacles with the electric riser. It enables an added 12 inches (305 mm) of extension and is the perfect complement to the already superior versatility of the DeckMaster or StreamMaster monitors.

### 3406 Electric Riser For DeckMaster & StreamMaster

- 3" waterway
- 12" extension
- With unique three-piece design, the extremely compact device is only 18 1/2" (470 mm) when nested
- Can be utilized within pump modules that have limited space
- Electrically actuated (12 or 24 volt - Must specify)
- Durable lightweight Pyrolite® construction
- Manual override
- 5 year warranty
- Inlet option: 3" (75 mm) victaulic or NPT (Must specify)
- Outlet options 3" (75 mm) or 4" (100 mm) flange (Must specify)



Electric Riser for DeckMaster

Electric Riser shown in extended position with Style 3440 DeckMaster and Style 5075 Akromatic 1250 Nozzle

Style	Weight lbs. (kg)	Height	Width	Depth	Inlet	Outlet	Flow	
							GPM	LPM
3406	38 (173 kg)	18 1/2" (470 kg)	11 1/16" (297 mm)	12" (305 mm)	3" (75 mm) NPT or VIC	3" or 4" FL (75 mm or 100 mm)	1250*	4800

\* For 3440 \*\*For 3578

"Quality and Innovative Fire and Rescue Equipment"



[www.bigredtruck.com.au](http://www.bigredtruck.com.au)  
07 3287 5504

