



## Forestry Monitor

### STYLE 3462

The 3462 Forestry Monitor is the latest addition to the Akron Brass electric monitor family. The 3462 provides an extremely rugged durable design ideal for brush and wildland firefighting. This compact monitor features a fully sealed integrated electrical control system with waterproof locking connectors for all motors, power and control connections to withstand harsh environments. The high speed motors provide proportional speed control for pinpoint stream positioning and accuracy. With a wide range of available nozzles, the 3462 is ideal for use in water, foam and CAFS applications.



#### Standard Features:

- CAN proportional speed joystick control
- Lightweight Pyrolite® construction
- Integrated and sealed electronics
- Waterproof (IP 67 rated) locking connectors
- Simple “plug and play” installation
- 320° maximum rotation range with stops at +/- 90°
- 135° maximum elevation range with stops at +45° and -20°
- 12V or 24V option

#### Nozzle Options:

- Style 3293 low flow adjustable electric fog nozzle with flush 30-60-95-125 gpm (115-230-360-475 lpm)\*
- Style 3293 mid flow adjustable electric fog nozzle 125-175-250-300 gpm (475-660-950-1140 lpm)\*
- Style 3293 Fixed orifice fog nozzles (must specify flow and pressure)\*
- Quick Attack™ foam tube attachments for Style 3293 fog nozzles
- Smooth bore tips

#### Additional Options:

- 2” quick disconnect
- Wireless remote control (CAN interface)
- 2” Electric Valve

\* Flat disperse fog pattern available on all Style 3293 nozzles



**Style 3462**  
Shown with 3293  
125-300 gpm Nozzle



**Style 6035**  
CAN Joystick



**Style 6037**  
Optional CAN  
Wireless Remote




Optional Quick Disconnect




**AKRON**  
BRASS COMPANY



Style 3462 with 3293 in a Narrow Fog Pattern



Top View  
(Less Nozzle)



Side View  
(Shown with Style 3293 Nozzle)




"Plug and play" connectors



Style 3293 Nozzle with Adjustable Baffle

### Friction loss



Nozzle Style	Pressure	Flow Setting gpm (lpm)	Effective Reach ft (m)	Overall Reach ft (m)
3293	100	30 (115)	74 (23)	84 (26)
		60 (230)	104 (32)	117 (36)
		95 (360)	120 (37)	130 (40)
		125 (475)	125 (38)	135 (41)
		175 (660)	135 (41)	145 (44)
		250 (950)	155 (47)	170 (52)
		300 (1140)	164 (50)	175 (53)

WWW.AKRONBRASS.COM



**AKRON**  
BRASS COMPANY

ISO 9001:2000 Registered Company

In U.S./International  
Akron Brass Company  
PH: 330.264.5678  
FAX: 330.264.2944

In North America  
Call Toll Free  
PH: 1.800.228.1161  
FAX: 1.800.531.7335

**IN NORTH AMERICA CALL 1.800.228.1161 | FAX 1.800.531.7335**

© Copyright 2010 Akron Brass Company. All rights reserved. No portion of this can be reproduced without the express written consent of the Akron Brass Company. (08/10)