

The SaberJet Nozzle employs the latest in firefighting nozzle technology. The Single Shutoff SaberJet is a truly multi-purpose nozzle with the penetration of a solid bore tip and the advantages of a fog pattern. The Single Shutoff SaberJet has a unique three position handle and ball to give you solid bore, fog or closed positions. The nozzle is capable of operating efficiently at pressures as low as 50 psi to reduce firefighter fatigue, or up to 100 psi for maximum flow. This versatile nozzle is well suited for multiple applications. If you are looking for a multipurpose nozzle, look no further... SaberJet is your answer.







## **Mid-Range SaberJet Nozzles (SSO)**

• Compatible with Quick-Attack Foam Tube Style 768, See page 31

1532 Mid-Range SaberJet SSO Nozzle

1533 Mid-Range SaberJet SSO Nozzle with Pistol Grip

Style	Swivel Inlet	Length	Weight Lbs. (kg)	Tin Outline	Fog at 100 PSI (7 bar)	
	Swivel inlet			Tip Options	GPM	LPM
1532	1 1/2" (38 mm)	11 1/8" (283 mm)	5 3/4 (2.6 kg)	1/2", 5/8", 3/4", 7/8", 15/16", 1" * (13, 16, 19, 22, 24, 25 mm)	135	510
1533	1 1/2" (38 mm)	11 ½" (283 mm)	6 1/4 (2.8 kg)	1/2", 5/8", 1/4", 7/8", 15/16", 1" * (13, 16, 19, 22, 24, 25 mm)	135	510

<sup>\*</sup> Must Specify



Style 1536

# **High-Range SaberJet Nozzles (SSO)**

• Compatible with Quick-Attack Foam Tube Style 768, See page 31

1535 High-Range SaberJet SSO Nozzle

1536 High-Range SaberJet SSO Nozzle with Pistol Grip

Style	Swivel Inlet	Length	Weight Lbs. (kg)	The Outline	Fog at 100 PSI (7 bar)	
	Swivel inlet			Tip Options	GPM	LPM
1535	2 1/2" (65 mm)	11 <sup>3</sup> / <sub>4</sub> " (298 mm)	6 (2.7 kg)	3/4", 7/8", 15/16", 1" * (19, 22, 24, 25 mm)	135	510
1536	2 1/2" (65 mm)	11 3/4" (298 mm)	6 ½ (2.9 kg)	3/4", 7/8", 15/16", 1" * (19, 22, 24, 25 mm)	135	510

<sup>\*</sup> Must Specify





**Solid Bore** 



Fog





The patented SaberJet Nozzle employs the latest in firefighting nozzle technology. The Dual Shutoff SaberJet is our original multipurpose nozzle with both solid bore penetration and fog stream capability. It also gives you the ability to flow both at the same time. The Dual Shutoff SaberJet can operate efficiently at pressures as low as 50 psi for reduced firefighter fatigue, or up to 100 psi for maximum flow. This versatile nozzle is well suited for multiple applications, making it a truly multi-purpose nozzle.







ALL SABERJETS
NFPA
1964
COMPLIANT

Style 1512

Fog

**Solid Bore** 

Combination Stream (Dual Shutoff only)

### 1" SaberJet Nozzles (DSO)

• Compatible with Quick-Attack Foam Tube Style 777, See page 31

1" SaberJet Nozzle DSO with Pistol Grip

1513 1" SaberJet DSO Nozzle

Style	Swivel Inlet	Length	Weight lbs. (kg)	Tip Options	Fog at 100 PSI (7 bar)	
					GPM	LPM
1512	1" (25 mm)	10 <sup>1</sup> / <sub>2</sub> " (267 mm)	5 3/8 (2.4 kg)	3/8", 1/2", 5/8" * (9.5, 13, 16 mm)	60	230
1513	1" (25 mm)	10 1/2" (267 mm)	5 (2.3 kg)	3/8", 1/2", 5/8" * (9.5, 13, 16 mm)	60	230

<sup>\*</sup> Must Specify

#### 1 1/2" SaberJet Nozzles (DSO)

 Compatible with Quick-Attack Foam Tube Style 777, See page 31

1515 1 1/2" SaberJet DSO Nozzle

1520 1 1/2" SaberJet DSO Nozzle with Pistol Grip

Style	Swivel Inlet Length		Weight	Tip Options	Fog at 100 PSI (7 bar)	
		Service Co. 2 Sec. 1	lbs. (kg)		GPM	LPM
1515	1 1/2" (38 mm)	10 ½" (267 mm)	5 (2.3 kg)	3/8", 1/2", 5/8" * (9.5, 13, 16 mm)	95	360
1520	1 1/2" (38 mm)	10 ½" (267 mm)	5 3/8 (2.4 kg)	3/8", 1/2", 5/8" * (9.5, 13, 16 mm)	95	360

<sup>\*</sup> Must Specify

#### Mid-Range SaberJet Nozzles (DSO)

 Compatible with Quick-Attack Foam Tube Style 768, See page 31

1522 Mid-Range SaberJet DSO Nozzle

1523 Mid-Range SaberJet DSO Nozzle with Pistol Grip

Style	Swivel Inlet	Length	Weight	Tip Options	The second second	100 PSI bar)
			lbs. (kg)	350.00	GPM	LPM
1522	1 1/2" (38 mm)	11" (279 mm)	5 3/4 (2.6 kg)	3/4", 7/8", 15/16", 1" * (19, 22, 24, 25 mm)	135	510
1523	1 1/2" (38 mm)	11" (279 mm)	6 1/4 (2.8 kg)	3/4", 7/8", 15/16", 1" * (19, 22, 24, 25 mm)	135	510

<sup>\*</sup> Must Specify

## **High-Range SaberJet Nozzles (DSO)**

 Compatible with Quick-Attack Foam Tube Style 768, See page 31

1525 High-Range SaberJet DSO Nozzle

1526 High-Range SaberJet DSO Nozzle with Pistol Grip

Style	Swivel Inlet	Length	Weight lbs. (kg)	Tip Options	Fog at 1	
	Sept (Chapter Contest)	1 (1 (1 ( ) Health			GPM	LPM
1525	2 1/2" (65 mm)	11 5/8" (295 mm)	6 (2.7 kg)	3/4", 7/8", 15/16", 1" * (19, 22, 24, 25 mm)	135	510
1526	2 1/2" (65 mm)	11 5/8" (295 mm)	6 1/2 (2.9 kg)	3/4", 7/8", 15/16", 1" * (19, 22, 24, 25 mm)	135	510

<sup>\*</sup> Must Specify

## High-Range SaberJet Nozzles (DSO)

- Compatible with Quick-Attack Foam Tube Style 768, See page 31
- Saberjet with 1 1/8" tip ideal for CAFS

1527 High-Range SaberJet DSO Nozzle

• Specify 2 1/2" or 1 1/2" swivel inlet

High-Range SaberJet DSO Nozzle with Pistol Grip

Style	Swivel Inlet	Length	Weight lbs. (kg)	Tip Options	Fog at 100 PSI (7 bar)	
			tos. (kg)		GPM	LPM
1527	2 1/2" or 1 1/2"* (65 or 38 mm)	11 5/8" (295 mm)	6 (2.7 kg)	1 1/8" (29 mm)	135	510
1528	2 1/2" or 1 1/2"* (65 or 38 mm)	11 5/8" (295 mm)	6 ½ (2.9 kg)	1 1/8" (29 mm)	135	510

<sup>\*</sup> Must Specify



1528

