

Experts in water.

Single Stage Models

Single Stage models provide the versatility of high flow rates with strong pressure.

Twin Stage Models

Twin Stage models provide greater pressure which enables them to throw water further so you can stand further away when fighting a fire.

Superior Suction Lift

Excellent suction lift capability with the ability to self prime from 6m (5m on diesel models) for more versatile installation options.

Discharge Port Options

Choice of 3 or 4 way discharge port (dependent upon Firefighter model chosen) for easy installation with a choice of pipe sizes.

Improved Pump Efficiency

Patented floating castellated impeller neckrings front and back provide improved pumping efficiency, especially with gritty water, extended seal life and dramatically reduced engine wear.

Low Oil Protection

All petrol models have low oil protection. The engine will not start or run if the oil level is inadequate.

Reduced Engine Wear

Trust balanced impeller design reduces axial loads on the engine for extended engine life.

Excellent Corrosion Resistance

Pump casing, diffusers and impellers are manufactured from quality corrosion resistant grade aluminium with polyester coated pump casing interior for added corrosion resistance.

Large Priming and Drain Ports

For easy case priming and draining after use the priming and draining plugs are a quick release bayonet design where no tools are required. The incorporate a safety release mechanism to avoid releasing them when the pump is pressurised.

Easy Maintenance

Heavy duty wide vane impeller for longer life, improved performance and easier cleaning in the case of a blockage.

Herbicide/Insecticide Spraying

"V" models come with Viton seal, orings, gaskets and caps fitted for improved chemical resistance. Please seek specialist advice from your chemical supplier if pumping chemicals. Use of aggressive chemicals may void warranty.

Quality Engines

Davey Firefighter are available in hand (recoil) or electric start models. All electric start models (12V, 30Amp hour battery and leads required) come fitted with hand start mechanism so they can be started in the case of a flat battery





