

## NSR-9744XL

## Xtreme Lumens Metal Multi-Function Full-Size Dual-Light Rechargeable

MARKET APPLICATIONS DESCRIPTION

Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.

This full-size rechargeable metal multi-function Xtreme Lumens dual-light uses a CREE® LED rated at 650 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable beam rated at 275 meters. A 600 lumens unfocused floodlight is integrated in to the housing which is perfect for close-up illumination. Additionally both the flashlight (any brightness mode) and the floodlight can be turned on at the same time for maximum safety and versatility. The flashlight body switch provides momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. The second body switch operates the floodlight. The housing and tail-cap are made from air-craft-grade 6061-T6 aluminum and bezel is constructed from 316 stainless steel bezel. The housing, tail-cap and the bezel have a Type III hard anodized finish. Power comes from a rechargeable Lithium-ion battery.

ACE MATERIAL Aircraft grade 6061 T6 Aluminum

CASE MATERIAL Aircraft-grade 6061-T6 Aluminum with 316 Stainless Steel bezel all with Type III Hard Anodized Finish - Black

DIMENSIONS Length: 11.8 inches (300 mm) • Handle diameter: 1.2 inches (30 mm) • Head diameter: 1.6 inches (41 mm)

**WEIGHT** Weight: 17.5 oz. (496 g) with battery installed.

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating.

Cree® LED. Impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT Flashlight: High - 650 lumens, Medium - 300 lumens, Low - 100 lumens, Strobe - 300 lumens • Floodlight: 600 lumens •

Dual-Light: 600 lumens

**ON/OFF** First Body Switch - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe •

Second Body Switch - Floodlight • First & Second Body Switch - Dual-Light

**RUN-TIME** Flashlight: High - 4.5 hours, Medium - 9 hours, Low - 25.5 hours, Strobe - 9 hours • Floodlight: 4.5 hours • Dual-Light:

4.5 hours

**BATTERY** 2-cell, 6 Volt Lithium-ion battery pack

CHARGING Charger is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.

**FEATURES** • Super-bright Xtreme Lumens design

• CREE® LED technology – 50,000+ hours LED

- · Flashlight/Floodlight/Dual-Light
- Momentary or constant-on plus 3 brightness levels & strobe
- · Sharp focused flashlight beam
- · High-efficiency deep parabolic reflector
- Effective beam distance of 275 meters (over 902 feet)
- Unfocused wide-beam floodlight for close-up illumination
- Dual-Light (flashlight & floodlight at the same time) for maximum safety & versatility
- Aircraft-grade 6061-T6 aluminum housing/tail cap and 316 stainless steel bezel
- · Type III hard anodized finish
- · Non-slip grip
- Flashlight/strobe body switch
- Floodlight second body switch
- Waterproof
- Impact & chemical resistant
- Serialized for personal identification
- Powered by Lithium-ion rechargeable battery (included)

WARRANTY Limited Lifetime warranty • Lifetime on LED, housing, lens, electronics and switches. One year on battery pack and


chargers from date of purchase. Excludes normal wear and abuse.


**APPROVALS** 



**OPTIONAL ACCESSORIES** 

5 Bank Charger, Direct Wire Kit, USB Charging Cable, Red, Yellow & Blue Safety Cones





PDS\_NSR-9744XL\_140227\_A