



## Intrinsically Safe Polymer Penlights

These non-rechargeable penlights are cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. They are ultra-compact and super slim with a powerful light output designed to illuminate very tight spaces. The tail-cap switch provides momentary or constant-on functionality. Power comes from 2 AAA (5410) & 3 AAAA (5412) premium batteries (included).

**INTRINSICALLY SAFE**



**30  
or  
50 Lumens**

- cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present.
- Engineered polymer housing
- Powered by AAA/AAAA batteries



XPP-5410G

XPP-5412G

**XPP 5410 series**





**XPP 5410 series**



High-efficiency deep parabolic reflector

## Intrinsically Safe Polymer Penlights



XPP-5412G



XPP-5410G

### FEATURES

- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Engineered polymer housing
- Single tail switch
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Powered by 2 AAA batteries (5410) & 3 AAAA batteries (5412) included
- Limited Lifetime Warranty\*



XPP-5410G



XPP-5412G



High-efficiency deep parabolic reflector



Push-button tail-cap switch


### XPP-5410G SPECIFICATIONS

- Lumens: 30
- Run-time: 18 hrs
- Beam distance: 40 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 5.8in, head diameter: 0.9in, handle diameter: 0.7in, weight: 1.9oz



### XPP-5412G SPECIFICATIONS

- Lumens: 50
- Run-time: 13.75 hrs
- Beam distance: 50 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 6.8in, head diameter: 0.6in, handle diameter: 0.5in, weight: 1.5oz



### INCLUDED

- XPP-5410G**
- Flashlight
  - 2 AAA premium alkaline batteries

- XPP-5412G**
- Flashlight
  - 3 AAAA premium alkaline batteries

### SAFETY RATING

cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present.

Patent 7,738,229

Model	UPC 0 17398
XPP-5410G	80298 7
XPP-5412G	80299 4

**NIGHTSTICK 5410**

CLASS I DIV 1 GRPS A-D T3  
CLASS II & III DIV 1 GRPS E-G T135C  
CLASS I ZONE 0 AEx ia IIC T3 Ga  
CLASS I ZONE 0 Ex ia IIC T3 Ga  
Ex ia op is I Ma  
Ex ia op is IIC T3 Ga  
Ex ia op is I Ma  
Ex ia op is IIC T3 Ga  
Inherent ITS 13 ATEX27839X  
IECEx ITS 14.0036X  
-20°C ≤ Tamb ≤ +40°C  
1.5V/Cell AAA Alkaline  
SEE INSTRUCTION MANUAL MFG MM-YY

cETLus  
ID 4001184  
INTRINSICALLY SAFE  
SP170035 INDUSTRIAL

Complies to:  
ANSI/UL STD 913, ANSI/UL 60079-0,  
ANSI/UL 60079-11  
Certified to:  
CAN/CSA STD C22.2 NO 137  
CAN/CSA STD C22.2 NO 60079-0  
CAN/CSA STD C22.2 NO 60079-11  
CSA STD C22.2 NO 25

**NIGHTSTICK 5412**

CLASS I DIV 1 GRPS A-D T3  
CLASS II & III DIV 1 GRPS E-G T135C  
CLASS I ZONE 0 AEx ia IIC T3 Ga  
CLASS I ZONE 0 Ex ia IIC T3 Ga  
Ex ia op is I Ma  
Ex ia op is IIC T3 Ga  
Ex ia op is I Ma  
Ex ia op is IIC T3 Ga  
Inherent ITS 13 ATEX27839X  
IECEx ITS 14.0036X  
-20°C ≤ Tamb ≤ +40°C  
1.5V/Cell AAAA Alkaline  
SEE INSTRUCTION MANUAL MFG MM-YY

cETLus  
ID 4001184  
INTRINSICALLY SAFE  
SP170035 INDUSTRIAL

Complies to:  
ANSI/UL STD 913, ANSI/UL 60079-0,  
ANSI/UL 60079-11  
Certified to:  
CAN/CSA STD C22.2 NO 137  
CAN/CSA STD C22.2 NO 60079-0  
CAN/CSA STD C22.2 NO 60079-11  
CSA STD C22.2 NO 25

\*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Batteries, normal wear and abuse are excluded.



**WWW.BIGREDTRUCK.COM.AU**

