

### XPP-5410G

#### Intrinsically Safe Penlight

<b>MARKET APPLICATIONS</b>	Hazardous work environments, industrial, automotive, law enforcement, fire & rescue
<b>DESCRIPTION</b>	This non-rechargeable penlight is cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. It is ultra-compact and super slim with a powerful light output designed to illuminate very tight spaces. The tail-cap switch provides momentary or constant-on functionality. Power comes from 2 AAA premium batteries (included).
<b>CASE MATERIAL</b>	Engineered Polymer - Green
<b>DIMENSIONS</b>	Length: 5.8 inches (147 mm) • Head Diameter: 0.9 inches (23 mm) • Handle Diameter: 0.7 inches (18 mm)
<b>WEIGHT</b>	Weight: 1.9 oz. (54 g) with batteries installed
<b>LENS</b>	Unbreakable polycarbonate with scratch resistant coating
<b>LIGHT SOURCE</b>	Flashlight: CREE® LED Impervious to shock with a 50,000 hour lifetime
<b>LIGHT OUTPUT</b>	30 lumens
<b>ON/OFF</b>	Single Tail-Cap Switch - Momentary or Constant-on Flashlight
<b>RUN-TIME</b>	18 hours
<b>BATTERY</b>	2 Premium alkaline AAA batteries (included)
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present</li> <li>• CREE® LED technology – 50,000 + hours LED life</li> <li>• Momentary or constant-on flashlight</li> <li>• Sharp focused beam for illuminating tight spaces</li> <li>• Engineered polymer housing</li> <li>• Non-slip grip</li> <li>• Single body switch</li> <li>• Waterproof</li> <li>• Impact &amp; chemical resistant</li> <li>• Built-in pocket/belt clip</li> <li>• Includes 2 premium AAA alkaline batteries</li> </ul>
<b>WARRANTY</b>	Limited Lifetime warranty • Lifetime on LEDs, housing, lens, electronics and switches. Batteries, normal wear and abuse are excluded.

#### APPROVALS



<p>CLASS I DIV 1 GRPS A-D T3  CLASS II &amp; III DIV I GRPS E-G T135C  CLASS I ZONE 0 AEx ia IIC T3 Ga  CLASS I ZONE 0 Ex ia IIC T3 Ga  Ex I M1 Ex ia op is I Ma  Ex II 1 G Ex ia op is IIC T3 Ga  Ex ia op is I Ma  Ex ia op is IIC T3 Ga  Intertek ITS 13 ATEX27839X  IECEx ETL 13.0024X  -20°C ≤ Tamb ≤ +40°C  1.5V/Cell AAA Alkaline  CE 0359</p>	<p>cETLus  ID 4001184  INTRINSICALLY SAFE  SECURITE INTRINSEQUE</p> <p>Conforms to:  ANSI/UL STD 913, ANSI/UL 60079-0,  ANSI/UL 60079-11  Certified to:  CAN/CSA STD C22.2 NO 157  CAN/CSA STD C22.2 No 60079-0  CAN/CSA STD C22.2 No 60079-11  CSA STD C22.2 No 25</p>
---	---

