

XPP-5412G Intrinsically Safe Penlight

MARKET APPLICATIONS	Hazardous work environments, industrial, automotive, law enforcement, fire & rescue
DESCRIPTION	This non-rechargeable penlight is cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. It is ultra-compact and super slim with a powerful light output designed to illuminate very tight spaces. The tail-cap switch provides momentary or constant-on functionality. Power comes from 3 AAAA premium batteries (included).
CASE MATERIAL	Engineered Polymer - Green
DIMENSIONS	Length: 6.8 inches (173 mm) • Head Diameter: 0.6 inches (15 mm) • Handle Diameter: 0.5 inches (13 mm)
WEIGHT	Weight: 1.5 oz. (43 g) with batteries installed
LENS	Unbreakable polycarbonate with scratch resistant coating
LIGHT SOURCE	Flashlight: CREE® LED Impervious to shock with a 50,000 hour lifetime
LIGHT OUTPUT	50 lumens
ON/OFF	Single Tail-Cap Switch - Momentary or Constant-on Flashlight
RUN-TIME	13.75 hours
BATTERY	3 Premium alkaline AAAA batteries (included)
FEATURES	<ul style="list-style-type: none"> • cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present • CREE® LED technology – 50,000 + hours LED life • Momentary or constant-on flashlight • Sharp focused beam for illuminating tight spaces • Engineered polymer housing • Non-slip grip • Single body switch • Waterproof • Impact & chemical resistant • Built-in pocket/belt clip • Includes 3 premium AAAA alkaline batteries
WARRANTY	Limited Lifetime warranty • Lifetime on LEDs, housing, lens, electronics and switches. Batteries, normal wear and abuse are excluded.

APPROVALS



<p>CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV I GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga Ex I M1 Ex ia op is I Ma Ex II 1 G Ex ia op is IIC T3 Ga Ex ia op is I Ma Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27839X IECEx ETL 13.0024X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAAA Alkaline</p>	 ID 4001184 INTRINSICALLY SAFE SECURITE INTRINSEQUE Conforms to: ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 Certified to: CAN/CSA STD C22.2 NO 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25
0359	

FLASHLIGHT		
FL1 STANDARD	50 LUMENS	2m
	13.75h	1m
	50m	161cd

