

ntrinsically Safe olymer Dual-Light

Flashlight



Floodlight



Dual-Light



These non-rechargeable dual-lights are cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present. They each use a CREE® LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Power comes from 3 AA batteries (not included).

INTRINSICALLY SAFE















- cetlus, Atex, IECEx and MSHA listed intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present.
- Flashlight/floodlight/dual-light
- Beam distance rated at 170 meters
- Engineered polymer housing



XPP-5422G

XPP-5422B









High-efficiency deep parabolic reflector

Intrinsically Safe Polymer Dual-Light





XPP-5422G

XPP-5422B

FEATURES

- Flashlight floodlight dual-light
- CREE® LED technology 50,000 + hours LED life
- · Momentary or constant-on flashlight
- · Sharp focused beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- . Dual-light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- · Non-slip grip
- . Dual body switches
- Waterproof
- Impact & chemical resistant
- · Built-in pocket/belt clip
- · Includes removable lanyard
- · Requires 3 AA batteries (not included)
- · Available in black & green
- Limited Lifetime Warranty*



Built in pocket/belt clip



Dual body switches



Wide-beam floodlight

Bayco Products, Inc. Permissible Nightstick 5422 Flashlight/Floodlight MSHA APPROVAL No. 20-A130001-0 TESTED FOR EVERMISC SAFETY IN METHANE-ASK MIXTURES ONLY DERVISE. A sponwed for use with three AA Deviced Type P01500, Emergion Type EMER, and Emergion Type attended only and the Authorities of Shah also only and register all transfers at the same time. Do not mit between different memoritariances or of different types. Lincoln (Spirities 5422 man and as appeared to year white permissibility is required. JUMI OF LEAR AND TO SEE AND SEE TO SEE AND SEE

SPECIFICATIONS

- Lumens: flashlight-120, floodlight-120, dual-light-240
- Run-time: flashlight-17.5 hrs, floodlight-17.5 hrs, dual-light-4.5 hrs
- · Beam distance: 170 meters
- · Water rating: IP-X7 waterproof
- . Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 6.9oz



INCLUDED

- · Flashlight with built-in pocket/belt clip
- · Removable lanyard

SAFETY RATING

cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present



Model UPC 0 17398

XPP-5422G 80093 8

XPP-5422B 80094 5

"Limited Lifetime Warranty - Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Bafferies, normal wear and abuse are excluded.



