

## NSR-9514B

### Polymer Multi-Function Duty / Personal-Size Flashlight Rechargeable



<b>MARKET APPLICATIONS</b>	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
<b>DESCRIPTION</b>	The NSR-9514B rechargeable glass-filled nylon polymer LED flashlight, offers 3 microprocessor-controlled brightness modes as well as a strobe function. Utilizing a CREE® LED, the 9514B has an impressive runtime of 4.25 hours in full-brightness mode. The 350 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 313 meters...that's over 1,026 feet. The 9514B has a two button design, a switch located on the waterproof body of the light and one in the tail cap. Both switches operate in tandem with one another.
<b>CASE MATERIAL</b>	Glass-filled Nylon Polymer w/ Aircraft-grade 6061-T6 Aluminum Tail Cap and a 316 Stainless Steel bezel both with a Type III Hard Anodized Finish - Black
<b>DIMENSIONS</b>	Length: 8.9 inches (226 mm) • Handle diameter 1.2 inches (30 mm) • Head diameter 1.6 inches (41 mm)
<b>WEIGHT</b>	Weight: 10.1 oz. (286 g) with battery installed.
<b>LENS</b>	Unbreakable polycarbonate with scratch resistant coating.
<b>LIGHT SOURCE</b>	Cree® LED. Impervious to shock with a 50,000 + hour lifetime.
<b>LIGHT OUTPUT</b>	High-Brightness - 350 lumens • Medium-Brightness - 200 lumens • Low-Brightness 55 lumens • Strobe - 300 lumens
<b>ON/OFF</b>	Single Body Switch & Single Tail Switch (Tandem Functionality) - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe
<b>RUN-TIME</b>	High-brightness - 4.25 hours • Medium-brightness - 8.5 hours • Low-brightness - 32.5 hours • Strobe - 5.5 hours
<b>BATTERY</b>	2-cell, 3.7 Volt Lithium-ion battery pack.
<b>CHARGING</b>	Charging platform is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• CREE® LED technology – 50,000 + hours LED life</li> <li>• Momentary or constant-on plus 3 brightness levels &amp; strobe</li> <li>• Sharp focused beam</li> <li>• Glass-filled nylon polymer housing</li> <li>• Aircraft-grade 6061-T6 aluminum tail-cap and 316SS stainless steel bezel both with a Type III hard anodized finish</li> <li>• Non-slip grip</li> <li>• Body &amp; tail switch</li> <li>• Waterproof</li> <li>• Impact &amp; chemical resistant</li> <li>• Serialized for personal identification</li> <li>• Powered by rechargeable Lithium-ion battery (included)</li> <li>• Includes wall or vehicle mounted charger as well as AC and DC power supply and anti-roll ring</li> </ul>
<b>WARRANTY</b>	Limited Lifetime warranty • Lifetime on LED, housing, lens, electronics and switches. One year on battery pack and chargers from date of purchase. Excludes normal wear and abuse.

#### APPROVALS



#### OPTIONAL ACCESSORIES

5 Bank Charger, Direct Wire Kit, USB Charging Cable, Red, Yellow & Blue Safety Cones



Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS\_NSR-9514B\_140227\_A