AIR ASPIRATING NOZZLES



4003

INLET: 3/4" (19 mm) GHT Female

GPM: 3 at 60 PSI

EFFECTIVE REACH

OF STREAM:

25' (8 M) at 60 PSI

MAXIMUM SAFE

OPERATING PRESSURE:

200 PSI (14 BAR)

DIMENSIONS:

length 5.60" (142.2 mm), weight 0.15 lbs (0.06 kg)



4015

INLET: 3/4" (19 mm) GHT Female

GPM: 8 at 60 PSI

EFFECTIVE REACH

OF STREAM:

35' (10 M) at 60 PSI

MAXIMUM SAFE

OPERATING PRESSURE:

200 PSI (14 BAR)

DIMENSIONS:

length 10" (254 mm), weight 0.20 lbs (0.10 kg)



4020

INLET: 1-1/2" (38 mm) Female

GPM: 15 at 100 PSI

EFFECTIVE REACH

OF STREAM:

60' (18 M) at 100 PSI

MAXIMUM SAFE

OPERATING PRESSURE:

200 PSI (14 BAR)

DIMENSIONS:

length 17.38" (441.45 mm),

weight 0.75 lbs (0.34 kg)



4025

INLET: 1-1/2" (38 mm) Female

GPM: 30 at 100 PSI

EFFECTIVE REACH

OF STREAM:

60' (18 M) at 100 PSI

MAXIMUM SAFE

OPERATING PRESSURE:

200 PSI (14 BAR)

DIMENSIONS:

length 17.38" (441.45 mm), weight 0.75 lbs (0.34 kg)

AIR ASPIRATING NOZZLES

4030

INLET: 1-1/2" (38 mm) Female

GPM: 50 at 100 PSI

EFFECTIVE REACH

60' (18 M) at 100 PSI OF STREAM:

MAXIMUM SAFE

200 PSI (14 BAR) **OPERATING PRESSURE:**

length 21.5" (546.10 mm), DIMENSIONS: weight 1.10 lbs (0.50 kg)

4031 / 4031S

1-1/2" (38 mm) Female INLET:

GPM: 50 at 100 PSI

EFFECTIVE REACH

OF STREAM:

60' (18 M) at 100 PSI

MAXIMUM SAFE

200 PSI (14 BAR) **OPERATING PRESSURE:**

14.75" (374.65 mm), DIMENSIONS: weight 0.75 lbs (0.34 kg)

4033

INLET: 1-1/2" (38 mm) Female

GPM: 70 at 100 PSI

EFFECTIVE REACH

OF STREAM:

60' (18 M) at 100 PSI

MAXIMUM SAFE

200 PSI (14 BAR) **OPERATING PRESSURE:**

length 21.5" (545 mm), DIMENSIONS: weight 1.10 lbs (0.5 kg)

4034 / 4034S

INLET: 1-1/2" (38 mm) Female

GPM: 70 at 100 PSI

EFFECTIVE REACH

60' (18 M) at 100 PSI OF STREAM:

MAXIMUM SAFE

200 PSI (14 BAR) OPERATING PRESSURE:

length 14.75" (375 mm), DIMENSIONS: weight 0.75 lbs (0.34 kg)







