

## PORTABLE FOAM SYSTEMS



## **Foam Eductor Backpack Systems**

With portable foam systems, every fire hose line becomes a foam line. For versatility and flexibility Scotty has eight different flow rates. All units include:

- · Backpack with 5 gallon capacity
- · Foam pickup hose with foam control quick connector
- Air aspirating nozzle with matching foam eductor
- · D-Handle shut-off with pistol grip, 1-1/2" thread

The first 4 digits correspond to the air aspirating nozzle included; the last two digits indicate the flow rate (gpm).

Systems available with NPSH, NHT(A) and BSP(B) threads. (Please indicate threads when ordering from your distributor).

## **Optional Variable Checkvalve**

The Back Pack systems can be fitted with the 4064 Variable Checkvalve foam control unit. This extra option gives the operator the ability to control the foam percentage being educted. The presets are OFF, .5%, 1% and 3%.

| Model     | Flow Rate         |
|-----------|-------------------|
| 4020BP15  | 15gpm - 57 l/min  |
| 4025BP30  | 30gpm - 114 l/min |
| 4030BP50  | 50gpm - 190 l/min |
| 4031SBP50 | 50gpm - 190 l/min |
| 4033BP70  | 70gpm - 256 l/min |
| 4034SBP70 | 70gpm - 256 l/min |
| 4035MBP70 | 70gpm - 256 l/min |
| 4037MBP   | 70gpm - 256 l/min |

Equipped with Fog/Straight stream nozzle tip.

S = Stubby Nozzle M = Medium Expansion



## 4064

For more information please see Pg. 12

The illustration at right shows a Scotty Foam Backpack System





