



PORTABLE ROLL & FOAM

4045A-30

"Roll & Foam" Mobile Foam Attack System

The Scotty 4045A-30 Roll & Foam Mobile Foam Attack System is a self-contained unit that can transform any pressurized fire hose, water supply line or stand pipe into a fire fighting foam generating station. An average person can roll the unit to a pressurized water source near a fire scene even when the tank is filled to capacity with fire fighting foam concentrate (foam concentrate not included). By following the instructions on the top of the tank, the user can deploy, the system and spray foam in under a minute.

The Scotty 4045-30 Roll & Foam can be installed in an accessible area and quickly deployed in case of an emergency. The unit can be used in industrial sites, installations, warehouse and storage facilities, schools, shopping malls. For marinas, harbors or aircraft hangars. The 4045A-30 can be configured for Class B.

The system consists of a wheeled supply tank with a 14 gallon capacity, a 50-foot length of flat hose, a 30gpm Scotty Foam Eductor factory set for either 1% for Class A foam (4045A-30) or 3% for Class B foam (4045B-30), a matching Air Aspirating Foam Nozzle and a D-Handle, Pistol Grip Shut-Off with swivel connector. The eductor is designed for a nominal operating pressure of between 50 and 100psi. The supply tank must be filled with foam concentrate prior to deployment. The threads on the swivel connector on the Eductor are standard 1-1/2" NPSH thread type. The user must confirm thread type compatibility between the unit and the water supply prior to installation. A Thread Adaptor is included to change to NHT(NST) thread.

The eductor, pistol grip shut-off and base of the nozzle are made from glass-reinforced engineering grade nylon, making it extremely durable and resistant to corrosion. The barrel of the nozzle is made from high-impact ABS polymer. The 14 gallon (53 Litre) foam container is made of polyethylene.

- Unit Weight: 22 lb. (Empty)
- Unit Dimensions: Height 34 inches x Length 19 inches x Width 15-1/2 inches
- A fabric dust cover is available for the unit, stock code 4045CVR



- Flow Rate of 30gpm, pressures from 50psi to 150psi.
- Suitable for industrial sites and installations, warehouse storage facilities, lumberyards, mines, shopping malls, schools, marinas, harbors or aircraft hangars.
- Portable, lightweight and made of corrosion-proof materials.

6

"Quality and Innovative Fire and Rescue Equipment"



www.bigredtruck.com.au

