

ACCESSORIES



4093

Rescue Rope Bag

15m x 7mm 250 kg test

50' x 9/32 550lb test

Braided MFP Polypropylene floating rope. Bright orange nylon and polyester self-draining bag c/w adjustable strap and 3M reflective safety band.



4089F, 4089M & 4089AF, 4089AM

Quarter Turn Quick Connect / Instantaneous

The 4089 eliminates problems associated with incompatible threads, damage from wear or cross-threading. The best benefit of this product is the speed in which hoses, nozzles and couplings can be connected and disconnected. Made from the same high quality, glass-filled nylon as other Scotty Firefighter products, the 4089 can withstand the rigors and demands of the firefighting environment. Made from Ny-Glass, the 4089 is durable, lightweight and will never corrode or seize.

4089A- is NHT.



4089A - Orange



4078

Stream Straightener

A double male threaded union, with built-in stream straightening vanes.

Tests have shown that when used on the discharge end of a hose just before the nozzle, a stream straightener will correct the water flow creating greater reach of stream, in some instances up to 20% more reach. The 4078 is available with 1-1/2" NHT (4078AA), NHT x NPSH (4078AC) and NPSH x NPSH (4078CC) threads.



4056

Scotty Squall Wall™

The Scotty 4056 is an easy to use device that creates a wall of water to help cool and protect structures. When connected to a water supply hose the angled ramp within the unit directs the water flow up through the opening vent. Depending on flow and pressure, the Squall Wall can create a wall of water up to 40 feet wide and 20 feet high. The Squall Wall™ can be secured to the ground with a spike or to a plywood plate for fast deployment. It can also be pre-positioned and permanently mounted on rooftops, walls, and gantries, even in trees. The Squall Wall™ is available in three different flow rates: 15gpm, 30gpm and 50 gpm at 100 psi. The 4056 come in the following configurations:

4056**	Male 1-1/2" NPSH threads
4056-**A	Male 1-1/2" NHT threads
4056-**AF	Female 1-1/2" NPSH threads (4086 Connector)
4056-**F	Female 1-1/2" NHT threads (4085Connector)
4056-**QC	Quarter Turn Quick Connect (4089F Quick Connect)
4056-**TA	with 1-1/2" NHT Tee
4056-**TC	with 1-1/2" NPSH Tee

** indicates a flow rate of either 15gpm, 30gpm or 50gpm



4056 Spray Pattern

"Quality and Innovative Fire and Rescue Equipment"



www.bigredtruck.com.au

