

## 4037-15,30,70 & 95

### Fog/Straight Stream Nozzle D-Handle Combination

The Scotty Combination Fog/Straight Stream Nozzle with D-Handle shut-off has superior characteristics to work with today's Class A and Class B foams. Designed for flexibility, the nozzle tip can be detached so a Scotty Foam eductor can be inserted between the tip and shut-off valve.

Available with 1-1/2" NHT, NPSH or BSP swivel connections. Manufactured from glass-reinforced polymer, this lightweight unit is ideal for today's needs.

## 4038-15,30,70 & 95

### Fog/Straight Stream Nozzle with Shut-Off

Built-in twist-to-shut-off capability. Ideal for hose stations, industrial uses, forestry and fire departments.

Available with 1-1/2" NHT, NPSH and BSP thread.

## 4006

### "Pincher" Dual Pattern Nozzle

The Scotty 4006 "Pincher" Nozzle is a flexible tipped nozzle that the user can simply squeeze between the fingers to change the spray pattern from a straight stream to a fan or slot pattern. The "Pincher" Nozzle is manufactured from glass-reinforced, engineering grade polymers. Using this material makes the Scotty 4006 very lightweight, extremely durable and absolutely corrosion proof. The nozzle can be used with Class A or Class B foams, but is not designed to generate the type of bubble structure typical of our air-aspirating foam nozzles.

The 4006 Nozzle comes with 1.5" Female NPSH threads or NHT threads (4006A).

The 4006 and 4006A also comes with a stream straightener to decrease flow turbulence and increase the reach of stream. It is rated for pressures up to 200 psi.

The 4006 can be purchased with a 4080 D-Handle pistol grip shut off shown at left.

## 4039MX

### "Foam Maker" Nozzle

The 4039MX medium expansion foam attachment is designed to fit the Scotty 4037 and 4038 Fog Nozzles, and also fits the UFS 1575 Fog Nozzle. Generating a 5" (120mm) thick stream of medium expanded foam, it will quickly lay down a foam firebreak for forest and grassland fires. Can be used against car fires, tire fires, haz-mat or any situation where a thick smothering foam blanket is required.

**4039MXPLUS** 4039MX and a 4037-70 (NPSH)

**4039MXPLUSA** 4039MX and a 4037-70A (NHT)

## 4005

### Penetrator Nozzle

The Scotty Penetrator Nozzle is specifically designed with a 1/4" discharge orifice. When connected to the end of a fire hose, it generates a high-velocity water jet. The pencil thin water jet penetrates the duff in Wildland fire, extinguishing deep-seated fires. When used in conjunction with Class "A" foam this nozzle is an extremely effective tool on duff fires. Comes with 1-1/2" double female connector. Please specify 4005 for NPSH or 4005A for NHT when ordering.

## 4032-50 & 4032-100

### Smooth Bore Nozzles

Smooth Bore Nozzles will direct a solid stream of water to its maximum reach with the pressure available. The nozzle barrels are made from Ny-Glass for resilience and durability, making them foam compatible and 100% corrosion-proof. The 4032-50 will flow 50 gpm (190 l/m) and has a 0.550" opening. The 4032-100 will flow 100 gpm (380 l/m) and has a 0.775" opening. Please specify 1-1/2" NHT or NPSH threads when ordering.



(Shown with optional 4080 D-Handle Shut off)

4039MXPLUS



(Shown with optional 4080 D-Handle Shut off)

