



# Solberg Asia Pacific Pty Ltd

## Technical Information

---



### Solberg Fire-Brake™ 3150A Class A Foam Concentrate

#### Description

Solberg Fire-Brake™ 3150A is a synthetic foam concentrate designed for Class A fires. When proportioned with water and applied with conventional fire fighting equipment, Fire-Brake™ is an outstanding Class A agent. This Class A foam provides optimum penetrating and wetting qualities on combustible solids such as wood, tyres and paper. This product is an effective water management tool. Solberg Fire-Brake™ 3150A provides traditional Class A and bushfire fighting foam (BFFF) performance.

---

#### Typical Physicochemical Properties

---

*(Not for specification purposes)*

Appearance:	Clear to straw-coloured liquid
Nominal use concentration:	0.1-1.0%
Specific Gravity @ 20°C:	1.02
Viscosity (Kinematic) @ 20°C:	4.5 Centistokes
Minimum use temperature	1.7°C
Surface Tension (1% solution)	< 25mN/m
Storage Temperature:	1.7° - 49°C
Freeze Point:	- 10°C

#### Applications

Synthetic foam concentrate for wildfires and other Class A materials. For use in fire fighting equipment such as hose lines, helicopter buckets, aerial water bombers and other water-carrying vehicles. Foam can be generated for extinguishing purposes through air aspirating and fog nozzles. When foam solution is dropped from the aircraft, foam will be generated by a shearing effect of air. For optimum performance, concentrate is to be mixed at a ratio of 1 litre of concentrate to 99 litres of water. Use a proportioner for best results. Concentrate can be used at lower levels to produce effective foam.

Solberg Fire-Brake™ 3150A is an excellent tool for structural fire fighting which can be applied through sprinkler systems, fixed and any water delivery system. This product has been used on house fires for proven extinguishment and also for minimising water use and associated damage.



# Solberg Asia Pacific Pty Ltd Technical Information



## Features

**Effective:** Solberg Fire-Brake™ 3150A will make your water last 2 to 10 times longer. Rapid extinguishment reduces the chances of dangerous incidents and reduces the risk to property and equipment.

**Reliable:** Fire-Brake™ products are manufactured to ISO 9001 requirements.

**Economical:** Fire-Brake™ 3150A is highly concentrated and will be effective at concentrations of 0.1 to 1.0%.

**Approvals:** USFS Qualified Products List (QPL).

## Storage

Solberg Fire-Brake™ 3150A may be stored for at least 10 years in its shipping container without change in its original physical or chemical characteristics. In foam storage tanks the product has a shelf life of a minimum of 10 years under normal conditions. It does not show significant sedimentation or precipitation in storage or after temperature cycling. Freezing and thawing have no effect on performance. The concentrate proportions satisfactorily in fire protection systems. No foam concentrate should be mixed in storage with other agents.

## Packaging

Solberg Fire-Brake™ 3150A is available in standard 20 litre pails and 200 litre drums. Bulk container delivery may be available.

## Warranty and Limited Remedy

Solberg Asia Pacific Pty Ltd warrants that Solberg Products will conform to Solberg specifications for Products at the time of shipment to Buyer. Solberg MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a Solberg Product is found not to conform to this warranty, BUYERS EXCLUSIVE REMEDY, AT SOLBERG'S OPTION, SHALL BE REFUND THE PURCHASE [PRICE OF OR REPLACE THE QUANTITY OF SOLBERG PRODUCT SHOWN TO BE NONCONFORMING. SOLBERG has no obligation under this warranty with respect to Product that has been modified or damaged through misuse, abuse, accident, neglect, or mishandling by Buyer. For other terms and conditions of sale, see General Terms and Conditions of Sale Applicable to Orders for Commercial products of the Solberg group of companies.

Solberg Asia Pacific Pty Limited  
[ABN 27 124 181 791]  
3 Charles Street  
St. Marys NSW 2760  
Australia  
Phone: (02) 9673-5300



Effective October 2007